



**Short and Medium Range  
Point-to-Point Unit**



**Long Range  
Point-to-Point Unit**

## Applications (PtP)

- Efficient multicasting of video using the **SkyWay-Videocast™** feature
- Wireless carrier / ISP backhaul
- Emergency / disaster recovery
- High throughput application such as Video Transfer
- Any application using Ethernet data transport.

## TECHNOLOGY SUMMARY

Continuing Solectek's tradition in high throughput, long distance wireless networking, the SkyWay 7000 Series builds upon the successful SkyWay Series products with a new, higher performance 5.8GHz wireless system.

With data rates to 108 Mbps and up to 400 mW of RF power, SkyWay 7000 delivers more capacity, farther than ever before. Such capability allows end-users to download large data files, high resolution images, video clips, and MP3 files within a matter of seconds. Streaming video and multiple VoIP connections can now be delivered or backhauled seamlessly.

Orthogonal Frequency Division Multiplexing (OFDM) technology delivers a wealth of benefits: high spectral efficiency supports class leading data rates while allowing multiple, nonoverlapping channels. OFDM is also capable of robust operation in near or non-line-of-sight (NLOS) link conditions, relaxing the stringent installation requirements associated with more traditional fixed wireless equipment.

Quality of Service (QoS) features within the SkyWay 7000 architecture allow tagged voice and video traffic to take priority over general data packet transfer, providing reliable, real-time capability even under congested link conditions. Priority privileges for marked frames are maintained from port to port: Ethernet through RF.

With security remaining a key consideration in many applications, the SkyWay 7000 delivers 128 bit AES encryption / decryption at full line speed. The AES algorithm was selected to be the standard encryption method of the US Government by the National Institute of Standards and Technology (NIST)

Physically, the SkyWay 7000 Series is fully integrated. The network engine, digital baseband, radio and antenna are all combined into a single, weatherized outdoor chassis, complete with Power over Ethernet (PoE) support. Guaranteed operational from -30C to +60C, the product can be installed at any convenient outdoor location needing only inexpensive Ethernet CAT5 cable for connection to an indoor network switch. To further assist installation, an integrated spectrum analyzer and audible antenna alignment function are provided as standard features.

The SkyWay 7000 is truly an enterprise class system that comes complete with full function bridge/router software and extensive network protocol and network management support.

Combining a high power, 108 Mbps OFDM radio with a high performance, QoS based bridge/router engine, the SkyWay 7000 Series is a powerful, yet easy-to-use product for all of your point-to-point and multipoint broadband wireless needs.

# Specifications

## SkyWay 7000 Professional Series PtP Link

**SOLECTEK**

www.solectek.com

Multipoint Performance	SkyWay 7101	SkyWay 7301	SkyWay 7501	SkyWay 7801
Link Distance*	4 Miles (6.4 km)	15 Miles (24 km)	30 Miles (48 km)	Antenna Dependent
Radio Power*	50 mW	400 mW	400 mW	400 mW
Radio				
Data Rate*	108 Mbps, 72 Mbps, 54 Mbps, 36 Mbps, 18 Mbps, 12 Mbps, 9 Mbps, 6 Mbps			
Modulation	OFDM - BPSK, QPSK, 16QAM, 64QAM			
Media Access	Prioritized CSMA/CA			
Frequency	5.470 - 5.875 GHz, country dependent			
DC Power	+48Vdc / 0.8A, via Power-over-Ethernet, indoor DC injector (included)			
Networking				
Ethernet	10/100Base-T, Auto-negotiating, Full/Half duplex, up to 100m separation between radio and network closet			
QoS	Line speed packet inspection of 802.1p, IP ToS, IP DiffServ tags			
	4 queue prioritization engine			
	RF MAC prioritization			
Frame Aggregation	Dynamic, User enable/disable			
Protocol Support	Transparent MAC layer bridging, IP Static Routing, RIP v1/v2 Transparent VLAN (802.1q)			
Management	HTTP Web Server, FTP, VLAN, SNMP v1/v2 with trap support and custom MIB, custom Event Log, Integrated Spectrum Analyzer, Audible Tone Alignment Function			
Security				
Encryption	Hardware accelerated, line speed 128-bit AES & 64, 128, 152-bit WEP			
Authentication	MAC address-based access control			
Channel Plan	Non-standard			

Mechanical	SkyWay 7101	SkyWay 7301	SkyWay 7501	SkyWay 7801
Configuration	Outdoor, Integrated Unit	Outdoor, Integrated Unit	Outdoor, Integrated Unit	Outdoor, Type-N Connector
Size	13" x 13" x 2.5"	13" x 13" x 2.5"	18" x 18" x 3.5"	10.25" x 10" x 3"
Weight	7.5 lbs	8.0 lbs.	14 lbs.	4.5 lbs.
Pole Mount Adapter	2-Axis Adjustment, Accommodates 1-3" pole diameter			
Environmental				
Temperature	-40° to +60° C			
Humidity	0-100% condensing			
Water/Dust	Meets IP67 requirements			
Lightning Suppression	Integrated, IEC 61000-4-5 Class 5 compliant			
Wind	125 MPH survivability, 110 MPH operation			
Wind Load @ 125 MPH	83 lbs.	83 lbs.	128 lbs.	
Regulatory				
Radio Compliance	FCC CFR47, 15.247			
	Industrie Canada RSS 210			
	China MII [2002] 277			
	EU: EN 60950-1, EN 61000-3-2, EN 61000-3-3, EN 301 489-1, EN 301 893			
	Mexico NOM; Cofetel			

\*Note: System performance and link distance for 36 Mbps/sec RF link rate setting. Throughput and link distance may be lower under NLOS conditions. Radio Power and data rate settings are subject to changes according to the country of installation.

### Solectek Corporation

6370 Nancy Ridge Dr. STE 109

San Diego, CA 92121

main: 858.450.1220

fax: 858.457.2681

info@solectek.com

[www.solectek.com](http://www.solectek.com)